

TKV-105-TB38V-MODUL



Features and benefits:

- Robust and durable
- Silicone switching elements
- MFII-layout with integrated 38 mm stainless steel trackball
- PS/2 and USB compatible
- Panel-mount version with mounting studs on rear-side
- Laser engraved key legends for excellent durability
- Non removable keycaps
- High operating comfort and good tactile feedback
- IP65 (NEMA 4x) sealing, water and dust proof
- >10 million operations per key
- Activation force 1 N / key travel 1.5 mm
- Semi or full customisation available

Specification

Number of keys:	105
Keyswitch Technology:	silicone switching element
Actuation Force/ -Travel:	1 N / 1.5 mm
Keyswitch Lifetime:	10 mil operations
Protection Level:	IP65, NEMA 4x
Mounting Type:	panel mount
Electronic Interface:	PS/2, USB
Dimensions:	446 x 145 x 36 mm 18.89" x 7.16" x 1.42"
Weight:	2650 g
Operating Temperature:	-40 °C to +90 °C -40 °F to +194 °F
Enclosure Material:	stainless steel

Specification Trackball

Ball Diameter:	38 mm (1.5")
Actuation Force:	50 g
Trackball Lifetime:	> 6 mil. Revolutions
Protection Level:	IP65 static (NEMA 4x), IP54 dynamic (NEMA 3/13)

Cat.-No.	Product Name	
KV14006	TKV-105-TB38V-MODUL-PS/2-US	PS/2; US-Layout
KV14008	TKV-105-TB38V-MODUL-USB-US	USB; US-Layout
KY14205	TKV-105-TB38V-MODUL-GASKET	Gasket

Other language versions/interfaces/configuration available on request



Tilauksesta

